

Description:

APEX UV1610 UV LED 打印机 打印尺寸 5~10 米 打印材料 各种材料 打印速度 10000 平方厘米/小时 打印精度 0.01mm

uv led 灯管 CE4 灯管 打印材料 各种材料 打印速度 10000 平方厘米/小时 打印精度 0.01mm

打印材料 UV 打印 APEX UV1610 打印材料 PVC uv 打印 uv 打印 uv 打印



TOSHIBA CE4 灯管 636nm 28KHZ 打印速度 3000 平方厘米/小时 8 平方厘米 5PL 打印精度

SGS 打印精度 0.01mm

OEM 打印精度 0.01mm

打印精度 0.01mm

RIP 打印精度 0.01mm

打印精度 0.01mm

Specification:

型号	UV1610
光源	UV LED 灯管
打印材料	各种材料
打印尺寸	62.99" * 39.37" / 160 * 100cm
打印速度	10000 平方厘米/小时
打印精度	0.01mm
功率	3800W
电压	50 / 60HZ 220V ±10% < 20A
温度	20~28C HR40-60
灯管	CE4 灯管 318X2 打印速度 5~10 米

RIP	SAi PhotoPrint DX Plus
	/ / / / / / / /
	Windows 7 / Windows 8 / Windows10
	UV
	KCMYWW / KCMYLcLmWW / KCMYLcLmWWV
	CISS
	USB3.0
	1200
	377 * 196 *162

Display:



Equipped with TOSHIBA CE4 Head ▲

High density nozzles, as many as 636, dot frequency is 28KHZ which will help to achieve a high print speed. Spray ink can reach 300 billion times without clogging and ablique, but with long durable life. 8 Levels grey scale, 5PL ink drop size, with a high resolution.



Easy Operation Control Panel ▲

Which will make you to use this printer without any confuse. Also all the button is installed with direction and different color to show its functions.



Low Water Indicator ▲

This Button will on if the water cooling system need to be refill with water.



Cleaning Button ▲

These two button will allow you to operate the cleaning easy.



Print Head Temp ▲

This indicator will show the status of the printer head.



Pressure Gauge ▲

It will show the Pressure the ink.



Certificated Ink ▲

Installed box for the ink bottle which is most space-saving and good looking. Also the Ink is get supplier certificated, pass SGS certification. Without any components which may damage print head, which will prolong the service life of the printer head. And the ink is high density and wide color gamut.



Professional Water Cooling System ▲

Water's high specific heat capacity, density, and thermal conductivity, allows water to transmit heat more easily. So it can more efficiently cool down UV LED light, in order to prolong its lifetime.



Vacuum Table ▲


Consists of a typically flat rigid surface in which exists small holes to evacuate air from under a workpiece, as to apply varying vacuum from between the desired workpiece and table to maintain a clamping force. To make the soft printing materials like leather more smooth and level, so as to get the best printing result.





Application:

Apex UV1610 UV



Warranty:

Microtec / Apex 产品 均享有 3 年质保 APEX UV 产品 均享有 5 年质保 Apex 产品 均享有 3 年质保

* 产品 均享有 3 年质保

* 产品 均享有 3 年质保

* 产品 均享有 3 年质保

* 产品 均享有 3 年质保