

48V  
 21A  
 1.25A  
 60W  
 RIPPLE & 2 150mVp-p  
 3 ±5.0  
 ±1.0  
 ±2.0  
 SETUP Note. 6 500 20 / 230VAC 500 20 / 115VAC 5 36V; 500 30 / 230VAC  
 500 30 / 115VAC 48V  
 50ms / 230VAC 16ms / 115VAC  
 4 90 264VAC 127 370VDC  
 47 63Hz  
 86  
 AC 1.2A / 115VAC 1A / 230VAC  
 30A / 115VAC 60A / 230VAC  
 0.25mA / 240VAC  
 110 150  
 55.2 64.8V  
 o / p  
 -30 + 70°C  
 20 90 RH  
 -40 + 80°C 10 95 RH  
 TEMP ±0.03 / °C 0 50°C  
 10 500Hz 2G 10 / 1 60min X Y Z  
 & EMC UL1310 2 LPV-60-5 CAN / CSA C22.2 223-M91 LPV-60-5 LPV-60-48 IP67  
 TUV EN60950-1 EN61347-2-13  
 WITHSTAND VOLTAGE I / P-O / P 3KVAC  
 I / P-O / P > 100M / 500VDC / 25°C / 70 RH  
 EMI CONDUCTION & EN55022 CISPR22 B  
 EN61000-3-2 Class A EN61000-3-3  
 EMS EN61000-4-2,3,4,5,6,8,11; ENV50204 EN55024 A  
 MTBF 732Khrs MIL-HDBK-217F 25°C  
 162.5 \* 42.5 \* 32mm \* \*



0.4Kg; 32/13.8 / 0.56CUFT