

CAN YOU PRINT 0~75CM HEIGHT MATERIALS?

YES WE CAN!

- TOSHIBA CE4M Print Heads, Fast Printing
- 2 in 1 multi-function platforms
- Print size: left side 800*1000mm + right side 600*800mm
- Print height: left side 0~100mm + right side 0~750mm
- Right side equipped with 65cm height adjustable lifting platform


Model No.: UV1610GM



Toshiba CE4 Print Heads Arrangement (5~12pcs Heads Options) UV1610GM: Single Head Single Color

Color configuration	Print Heads Quantity	Color Arrangement	Print Area
4color+1white	5pcs	K C M Y W	160*100cm
4color+1white+1varnish	6pcs	K C M Y W V	160*100cm
6color+1white	7pcs	K C M Y LC LM W	160*100cm
6color+1white+1varnish	8pcs	K C M Y LC LM W V	160*100cm
4color+2white	6pcs	K C M Y W W	160*100cm
6color+2white	8pcs	K C M Y LC LM W W	160*100cm
4color+2white+2varnish	8pcs	K C M Y W W V V	160*100cm
6color+2white+2varnish	10pcs	K C M Y LC LM W W V V	160*100cm
4color*2+4white	12pcs	K K C C M M Y Y W W W W	160*100cm

UV1610GM



Left platform:

Equipped with air suction device
0-100mm printing height
Max. print volume: W800*L1000*H100mm



Right platform:

Equipped with 0-650mm height
adjustable lifting system
Max. print volume: W600*L800*H750mm



- TOSHIBA CE4 Print Head
- High density nuzzles , faster printing with high resolution



Easy Operation Control Panel:

It is clear to use this printer without any confuse. Also all the button is installed with direction and different color label to show its functions.




1 2 IN 1 MULTIFUNCTIONAL PLATFORMS

Print Size: Left side 80*10cm + Right side 60*80cm
Print Height: Left side 0-10cm +Right Side 0-75cm
Right Side Equipped with 65cm Height Adjustable Lifting Platform

2 EQUIPPED WITH TOSHI-BA CE4 PRINT HEAD:

High density nozzles, as many as 636, dot frequency is 28KHZ which will help to achieve a high print speed. Spray ink can reach 300 billion times without clogging and ablique, but with long durable life. 8 Levels grey scale, 5PL ink drop size, with a high resolution.




FEATURES



Platform locating
function



Suction platform
segment control



Double
guide, double screw



X,Y axis uses three
groups of servo



Automatic height
detector, ink carriage
anti-collision



Ink carriage with
Anti-static device



Print Head Temp,
shows the temp
status of the
printer head, safer



The color
separation cleaning
device has high
washout rate and
better ink saving



Environmental
friendly LED-UV
curing



Support CMYK,
White and Varnish
synchronization
output



PROFESSIONAL R&D TEAM



OUR EXHIBITIONS



CUSTOMER VISITING



ENGINEERS ON-SITE SUPPORT

