Description:

Hover Heat Press□□ Auto Open Clam□ □□ □□□ □□□□. □ □□ □□□ □□□□ □□□□. □□ □□ □□ □□ □□ □□ □□ □□ □□□ □□ □□□ □ □□ □□□ □□□□□.

□ □□□□ □□□ □□ □□□ □□□ □□ □□□ □□ □□ □ □□□ □□□□. □□ □□ □□□ □□ □□□ □□□□ □□□ □ □□□□.

Feature:

* □□□□ □□ □□
* □□ □□ □□
* □□□ □□ & □□ □□□
* □□□ □□□□□ □□□ □□□
* □ □□ □□ - □□□ □□ □□□ □□ □□□ □□ □
* □□ □□□ □□□□□.
* □□ □□ □□ □□ □
* CE □□
* □□ □□ □□ □□ □
* □ □□□ □□ □□ - □□□□ □□□□ □□ □□ □ □□
* □□□ □□□ □□□ □□ 2.5 □□□□ □□□ □□ □□
* 3 / 16 "□□□ □□□ □□ □□
*□□ □□ □ & □□ □□ □□□
* 3 / 4 "□□ □□ □ □□ □
* □□ □□□□□□□ □□ □□
* 110V □□ 220V□□ □□ □□
* □□ □□□ □□ □ □□□

* □□ □□ □□□ □□□ □□□ □□

Specification:

□□ □□	□□, □□ □□□, □□ □
□□ □□	16 "* 20"(40 * 50cm)
□□ □□	GY-06 □□□ □□ & □□ □□ □□ □□ □□□□ □□□ □□□ □□ □□
□□ □	50□
□□ □□□ □□	□
□□	220V
□	1800W
□□ □□	0-999 □
□□ □□	225 C
□□ □□□	± 0.5 %
□□ □□	54 * 88 * 57cm
□ □□	60kg

□□. □□ □□ □□ □□□ □□	□□ 10mm □□ 5mm □□

Application:

1. DTG □□ □□□□ □□ □□ □□□ □□□ □□□□□□□□.
2. □□ □□□, □□ □□ □□.

Display:

Two modes - one for contact and the second for pressure
Six heights - Adjustable gear for easy heat platen height adjustments

UP to 6mm space for curing ink: The upper platen curing over the garment to ensure brighter color and a stronger bond between ink and the garment. With this breakthrough technology, you never have to worry about Direct-To-Garment ink residue on your platen.